

50 - 60 HP

DEUTZ-FAHR

4E KEYLINE SERIES



ROPS

Designed to simplify farming life, the popular Deutz-Fahr 4E Keyline Series features two models, 50 hp and 60 hp, and can be packaged with a 4-in-1 loader.

They are ideal for lifestyle and livestock farmers and specialist growers, made tough for Australian conditions, and can be used with a variety of mounted and towed implements.

Designed to have a front end loader fitted, forward/reverse shuttle synchronised transmission is equipped as standard across the whole range.



4050E

34KM/H

4060E

34KM/H

50HP

60HP

PHONE 1800 789 633




**WE WORK BEYOND
THE HORIZON.**



TECHNICAL DATA & FEATURES

4050E KEYLINE HD ROPS

4060E KEYLINE HD ROPS



POWER + PERFORMANCE		
Engine Type	Deutz Fahr SDF 1000 Series	
Emissions	Tier III A	
Cylinders / Capacity	3/3000	
Aspiration	Natural	Turbo Intercooler
Max Power - ECE R120 (kW/HP)	36.8/50	44.1/60
Max Torque (Nm)	184	221
Rated Engine Speed (rpm)	2200	
Fuel Capacity (l)	55	55
DRIVE + HANDLING		
Gearbox Type and Gears	Synchronised Shuttle	
Number of Gears	12+12	
Forward/Reverse Shuttle	■	
Clutch Type	Double Dry Heavy Duty 11"	
Min Speed (km/h)	0.5	
Max Speed (km/h)	34	
4WD	■	
Diff Lock	Mechanically Operated Rear	
Brakes (NO / Type)	2/ Girling Braking System	
Wheel Size - Rear	Adjustable 14.9*28	
Wheel Size - Front	Adjustable 11.2*20	
PTO Type	Mechanical Independent	
Speeds - Rear	540	
PTO engine speed (rpm)	1960	
LIFT + FLOW		
Type	Open Centre	
Flow Rate (l/min)	31	
Remote Valves (sets)	2	
Remote Valve Type	Detent/Spring	
3 Point Hitch Type	Mechanical with Draft	
Category	2	
Max Lift Capacity - Rear (kg)	1600	
COMFORT + CONVENIENCE		
2 Post ROPS	■	
Sun Canopy	■	
Driver Seat with Mechanical Suspension	■	
Display	Analogue	
Side Control Levers	■	
Flat Platform with Rubber Mat	■	
Upswept Side Mounted Exhaust	■	
Worklights (No + Type)	2 Bonnet / 1 Rear	
WEIGHTS + DIMENSIONS		
Wheelbase (mm)	1950	
Length (mm)	3513	
Min Overall Width (mm)	1831	
Height (mm)	2460	
Weight (kg)	2860	

CANOPY AND WHEEL WEIGHTS STANDARD



HEAVY DUTY THREE POINT LINKAGE



FORWARD/REVERSE SHUTTLE



SPACIOUS OPERATING AREA



INDEPENDENT PTO



■ Standard