

# 4060E Keyline HD

## 4WD ROPS



### Engine

SDF 1000 Series Tier 3 Diesel Engine  
3 Cyl/3000cc Turbocharged Intercooled  
Liquid/Oil Cooled  
Individual Bosch Injector Pumps  
60Hp @ 2350 rpm (2005/25/CE)  
Torque 221nm  
Up Swept Side Exhaust  
55lt Fuel Capacity

### Transmission

12/12 Synchronmesh Gearbox  
Forward/Reverse Synchro Shuttle  
Shuttle Lever Mounted on Steering Column  
Creep Range STD  
Double Dry Heavy Duty 11" Clutch  
Heavy Duty Rear Axle  
Rear Wheel Girling Brake System  
Front Wheel Assist  
Heavy Duty SDF Front Axle  
Front & Rear Diff Lock  
35 km/h Road Speed

### PTO

Independent Rear PTO  
540 Speed PTO  
540 @ 1965 Rpm  
1"3/8 -6 Spline PTO shaft

### Operator Environment

2 Post Foldable ROPS Frame  
Flat Platform  
Rubber Floor Mat  
Deluxe PVC Mechanical Seat  
Sun Canopy  
1 Rear Work Light  
2 Bonnet Lights with Hi/Lo Beam



### Hyd/Linkage/Drawbar

Open Centre Hydraulic System  
31 l/min Hyd Pump  
Separate 17 L/min Steering Pump  
2 Sets of Remotes - 1 Detent / 1 Spring  
Mechanical Three Point Linkage  
Position & Draft Control Settings  
CAT 2 Ball ends  
1600kg lift capacity  
Swinging Drawbar - CAT A

### Wheel Equipment & Miscellaneous

Fully Adjustable Wheels  
11.2\*20 Front -14.9\*28 Rear Ply Tyres  
172Kg Rear Wheel Weights

### Weights & Dimensions

Wheelbase	1950mm
Overall Length	3513mm
Overall Width	1831mm
Overall Height	2460mm
Total Weight	2860kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.

July 2022