## DEUTZ-FAHR 4E SERIES



Known for exceptional cab comfort, with car-like tech and features, the 4E Cabin Series offers three models ranging in output from 62 hp to 95 hp. Highly manoeuvrable and offered with STOLL loader options, standard features include engine speed programming, synchro shuttle with splitter, 4 wheel wet disc brakes and high capacity hydraulics.

Or choose the efficient 85 hp 4E ROPS, ideal for raking, slashing, feeding out and day-to-day farming tasks. With an ISO mounted platform, intuitive controls, clever ergonomics and remarkable visibility, the 4E ROPS carries many of the same features of a cabin tractor. All 4E series tractors are equipped with a forward / reverse shuttle synchronised transmission; a must when doing loader work.







TECHNICAL DATA & FEATURES	4065E CAB	4080.4E CAB	4090.4E ROPS	4100.4E CAB	
POWER + PERFORMANCE					
Engine Type	Deutz-Fahr SDF 1000 Series				
Emissions	Tier III A				
Cylinders / Capacity	3/3000 4/4000				
Aspiration	Turbo Intercooler				
Max Power - ECE R120 (kW/HP)	45.6/62	58.8/80	62.5/85	70/95	
Max Torque (Nm)	240	325	348	373	DEUTZ FAHR
Rated Engine Speed (rpm)		2200		2000	
Fuel Capacity (I)		70	1		
DRIVE + HANDLING					CAB MODEL
Gearbox Type and Gears	Synchronised Shuttle				
Number of Gears	30+15				C/T TT
Forward/Reverse Shuttle					
Clutch Type	Double Dry HD 11" Double Dry HD 12"				
Min Speed (km/h)	0.23				
Max Speed (km/h)	40				
4WD					
Diff Lock	Mechanically Operated Front + Rear				
Brakes (N0 / Type)	4/ Independent Wet Disc				ROPS MODEL
Wheel Size - Rear	Adjustable 340/85R28 Adjustable 420/85R30				
Wheel Size - Front	Adjustable 9.5R20 Adjustable 320/70R24				77
РТО Туре	Mechanical Independent				
Speeds - Rear	540 / 750				
PTO engine speed (rpm)	1967 / 1560				
LIFT + FLOW					
Type		Open C	entre		
Flow Rate (I/min)	Steering 17 / Hydraulic 42				
Remote Valves (sets)	2 3				FOUR WHEEL WET DISC BRAKES
Remote Valve Type	Spring 2 Detent + Spring / 1 Float				
3 Point Hitch Type	Mechanical with Draft				
Category	2				
Hitch End Type	Ball				
Max Lift Capacity - Rear (kg)	2500 3500				
COMFORT + CONVENIENCE					
Air-Conditioned Cabin			-		
Digital Climate Control	•		-		
2 Post ROPS	-	-	•	-	FORWARD/REVERSE SHUTTLE
Sun Canopy	-	-	•	-	SHUTTLE
Driver Seat w/ Mechanical Suspension		•			
Adjustable Steering Wheel					
Display	Analogue				
Side Control Levers					
Engine Speed Programming	-				
EASYLIFT Three Point Linkage					
Flat Platform Mounted on Silent-Block					
Upswept Side Mounted Exhaust					DIGITAL CLIMATE
		C-L:-	2 Bonnet / 1 Rear	2 Bonnet / 4 Cabin	CONTROL
Worklights (No + Type)	2 Bonnet / 4	Cabin	220		
Worklights (No + Type) WEIGHTS + DIMENSIONS	2 Bonnet / 4	Cabin			
	2 Bonnet / 4 1976	Cabin	2106		
WEIGHTS + DIMENSIONS Wheelbase (mm) Length (mm)		Cabin			(a) ≥ (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c
WEIGHTS + DIMENSIONS Wheelbase (mm)	1976	Cabin	2106		- 0 2 0 0 ·
WEIGHTS + DIMENSIONS Wheelbase (mm) Length (mm)	1976 3730	2666	2106 3990	2666	
WEIGHTS + DIMENSIONS Wheelbase (mm) Length (mm) Mid Overall Width (mm)	1976 3730 1800		2106 3990 1830	2666 3250 ■ Standard	