



Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc Turbocharged Intercooled
Liquid/Oil Cooled
Engine speed programming
Individual Bosch Injector Pumps
85Hp @ 2200 rpm (2005/25/CE)
Side mounted upswept exhaust – Tractor only
Side mounted down swept exhaust – Tractor + FEL
70lt Fuel Capacity

Transmission

30/15 Synchromesh Gearbox Forward/Reverse Synchro Shuttle Shuttle mounted on Steering Column Double Dry Heavy Duty 11" Clutch Gear Levers Located Right Hand Side Creep Gear Std Heavy Duty Rear Axle 4 Wheel Independent Braking Front Wheel Assist- Mechanical Front & Rear Diff Lock- Mechanical 40 km/h Road Speed

PTO

Independent Rear PTO 540/ 750 Speed PTO 540 PTO @ 1967 Rpm 540E PTO @1560 Rpm 1"3/8 -6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment 320/70R24 Front 420/85R30 Rear Front Weight Frame Dynamic Steering Fenders



Operator Environment

2 Post ROP Frame
Flat Floor ISO Mounted Platform
Rubber Floor Mat
Ergonomic Controls
Telescopic and Tilting Steering Wheel
Analogue Dash
Deluxe PVC Mechanical Seat
Sun Canopy
Telescopic Mirrors
1 Rear Work lights
2 Bonnet Work lights
Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
42 I/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT raise and lower switch
Position & draft control Settings
Cat 2 Ball ends
3500kg lift capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase 2106mm Overall Length 3990mm Total Weight 3100kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.