



Engine

SDF 1000 Series Tier 3 Diesel Engine 4 Cyl/4000cc Turbocharged Intercooled Liquid/Oil Cooled Engine Speed Programming Individual Bosch Injector Pumps 80Hp @ 2200 rpm (2005/25/CE) Torque 325nm Side Mounted Cabin Exhaust 70lt Fuel Capacity

Transmission

30/15 Synchromesh Gearbox
Forward/Reverse Synchro Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road Speed

PTO

Independent Rear PTO 540/ 750 Speed PTO 540 PTO @ 1967Rpm 540E PTO @1560 Rpm 1"3/8 -6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment 320/70R24 Front 420/85R30 Rear Front Weight Frame Dynamic Steering Fenders



Operator Environment

Air Conditioned Cab
Digital Climate Control
Ergonomic Controls
Adjustable Steering Column
Analogue Dash
Mechanical Sprung Cloth Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
42 I/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT Raise and Lower Switch
Position & Draft Control Settings
Cat 2 Ball Ends
3500kg Lift Capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase 2106mm Overall Length 3990mm Total Weight 3250kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.