





## **Engine**

SDF 1000 Series Tier 3 Diesel Engine 4 Cyl/4000cc Turbocharged Intercooled Liquid/Oil Cooled Engine Speed Programming Individual Bosch Injector Pumps 95Hp @ 2200 rpm (2005/25/CE) Side Mounted Cabin Exhaust 70lt Fuel Capacity

#### **Transmission**

30/15 Synchromesh Gearbox
Forward/Reverse Synchro Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road Speed

#### PTO

Independent Rear PTO 540/ 750 Speed PTO 540 PTO @ 1967Rpm 540E PTO @1560 Rpm 1"3/8 -6 Spline PTO Shaft

# Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment 320/70R24 Front 420/85R30 Rear Front Weight Frame Dynamic Steering Fenders

## **Operator Environment**

Air Conditioned Cab
Digital Climate Control
Ergonomic Controls
Adjustable Steering Column
Analogue Dash
Mechanical Sprung Cloth Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

## Hyd/Linkage/Drawbar

Open Centre Hydraulic System
42 I/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT Raise and Lower Switch
Position & Draft Control Settings
Cat 2 Ball Ends
3500kg Lift Capacity
Swinging Drawbar – CAT A

### **Weights & Dimensions**

Wheelbase 2106mm Overall Length 3990mm Total Weight 3250kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.