

102 - 126 ^{HP}

DEUTZ-FAHR

5G HD SERIES



CAB

If you're in the market for a universal tractor, the internationally renowned Deutz-Fahr 5G HD Series is worth serious consideration. Encompassing two models, 5105.4G and 5125G, delivering respective power outputs of 102 hp and 126 hp, the 5G HD tractors are perfect for livestock and arable farming, as well as vineyard operations.

Highly manoeuvrable, especially when fitted with a front end loader, the 5G HD tractors are packed with practical features, such as wet clutch Powershuttle, 4 wheel wet disc braking and Deutz-Fahr's Stop&Go technology. Loader work is made easy with integrated controls and the FARMotion common rail engine is economical to maintain and run.



5105.4G HD

40KM/H

102HP

5125G HD

40KM/H

126HP



PHONE 1800 789 633

**WE WORK BEYOND
THE HORIZON.**



TECHNICAL DATA & FEATURES
5105.4G HD CAB
5125G HD CAB

POWER + PERFORMANCE

Engine Type	Deutz-Fahr FARMotion	
Emissions	Tier III	
Cylinders / Capacity	4/3849	
Aspiration	Turbo Intercooler	
Max Power - 2000/25/EC (kW/HP)	76/102	93/126
Max Torque (Nm)	408	500
Rated Engine Speed (rpm)	2200	
Fuel Capacity (l)	150	

DRIVE + HANDLING

Gearbox Type and Gears	Wet Clutch Power Shuttle	
Number of Gears	40+40	60+60
Powershift Speeds	2	3
Speed Matching Powershift		■
Forward/Reverse Sense Clutch Shuttle	■	
STOP & Go	■	
Min Speed (km/h)	0.22	0.12
Max Speed (km/h)	40 ECO	
4WD + 4 Wheel Diff Lock	■	
Brakes (NO / Type)	4/ Independent Wet Disc	
Wheel Size - Rear	Adjustable 480/70R38	Fixed 540/65R38
Wheel Size - Front	Adjustable 420/70R24	Fixed 440/65R28
PTO Type	Electro-Hyd Independent Wet Clutch	
Speeds - Rear	540/540E/1000/1000E	
PTO engine speed (rpm)	1958/1650/1960/1643	

LIFT + FLOW

Type	Open Centre	On Demand
Flow Rate (l/min)	Mechanical / Steering 40 - Hydraulics 55	Mechanical / Steering 40 - Hydraulics 90
Remote Valves (Sets/Type)	3 / (1 Kickout / 1 Detent / 1 Float)	3 / (3 Float / 3 Detent)
Flow Control on Remote Valves	1 Valve	All Valves
3 Point Hitch Type	AGROTRONIC Electronic Hitch c/w external fender control	
Category	2	
Hitch End Type	Hook	
Max Lift Capacity - Rear (kg)	3600	5410

COMFORT + CONVENIENCE

Air-Conditioned Cabin	■	
Radio/MP3 Player	■	
Silent Block Cab Suspension	Optional	■
Cloth Driver Seat with Pneumatic Suspension	■	
Trainee Seat	Optional	
Adjustable Steering Wheel	■	
InfoCentre Dash	■	
Engine Speed Programming	■	
Hi Vis Roof	■	
SDD Steering	-	■
Upswept Side Mounted Exhaust	■	
Worklights (No + Type)	4 Bonnet / 4 Cabin	4 Bonnet / 6 Cabin



WEIGHTS + DIMENSIONS

Wheelbase (mm)	2400	
Length (mm)	4270	4314
Mid Overall Width (mm)	2186	2320
Height (mm)	2700	2730
Weight (kg)	4300	4400

■ Standard


COMFORTABLE WORKING AREA

INTEGRATED FRONT END LOADER CONTROL

SENSE CLUTCH POWERSHUTTLE

FARMOTION COMMON RAIL DIESEL ENGINE

ON DEMAND 90L/MIN HYDRAULICS (5125G)