



Engine

FARMotion Tier 3 Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
No AdBlue / No DPF
Liquid/Oil Cooled with Viscous Fan
High Pressure Diesel Injection Common Rail
126 Max Hp @ 2200 rpm (2000/25/CE)
6Hp Power Boost
Torque 508 Nm @1600 rpm
Engine Speed Programming × 2
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 200 Litres

Transmission

30/30 Forward/Reverse Gears
Wet Clutch Powershuttle
Shuttle Modulation – 5 Stage (Sense Clutch)
5 Speeds / 2 Ranges / 3 Stage Powershift
Automatic Powershift (APS)
Speed Matching
Comfort Clutch
Stop and Go Function
Front Wheel Assist – Push Button
4 Wheel Independent Braking
Hydraulic Parking Brake (HPB)
100% Front & Rear Diff Lock - Push Button
ASM Auto Diff Lock & 4WD Engagement
Front Axle Suspension
50 km/h Road Speed

PTO

Independent Wet Multidisc Clutch 4 Speed PTO 540/540E/1000/1000E Push Button Control in Cab/Fender Auto PTO Interchangeable PTO Spline Function 1" 3/8 – 6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment 440/65R28 Front -540/65R38 Rear 2310mm Rear Guard Extensions Front Weight Frame ISO 11786 7 Pin Socket + 12V Socket



Operator Environment

E class Air Conditioned Cab
Hydro Silent Block Cabin Suspension
Powershift Side Console with Lever Remotes
Max-Professional Air Seat
Tilt and Telescopic Steering Wheel
SDD Rapid Steering circuit
INFOCENTER Pro Digital Display
Trainee Seat with Seatbelt
MP3 Radio Player with Quad Speakers
Telescopic Mirrors
WOLP (Work Operating Light Panel)
8 Cabin Work Lights
2 Work Lights on Cab Post
4 Bonnet Front Work Lights
Rotating Beacon

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
120 L/min Hyd Pump
Free hydraulic oil return
4 Sets of Mechanical lever remotes
4 Float / 2 Detent
Flow Control on All Remotes
AGROTRONIC EHR with Position & Draft
External Raise & Lower on Rear Fenders
Cat II Hook Ends
5000 kg Lift Capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase 2550 mm Length 4428mm Total Height 2740mm Total Weight 5700 kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.