

6130 TTV 40km/h Variable



FARMotion Tier 3 Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
No AdBlue / No DPF
Liquid/Oil Cooled with Viscous Fan
High Pressure Diesel Injection Common Rail
126 Max Hp @ 2200 rpm (2000/25/CE)
6Hp Power Boost
Torque 508Nm @1600 rpm
Engine Speed Programming × 2
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 200 litres

Transmission

TTV 2 range Variable Transmission
3 Modes (AUTO, Manual, PTO)
Eco/Power Dial
Speed Cruise Control × 2
Active Stationary Control (Power Zero)
Wet Clutch Powershuttle
Shuttle Modulation – 5 Stage (Sense Clutch)
Front Wheel Assist – Push Button
4 Wheel Independent Braking
Hydraulic Parking Brake (HPB)
100% Front & Rear Diff Lock – Push Button
ASM Auto Diff Lock & 4WD Engagement
40km/h Road Speed @ Economy RPM

РТО

Independent Wet Multidisc Clutch 3 Speed PTO 540/540E/1000 Push Button Control in Cab/Fender Auto PTO Interchangeable PTO Spline Function 1" 3/8 – 6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment 440/65R28 Front -540/65R38 Rear 2310mm rear guard extensions Front Weight Frame ISO 11786 7 Pin Socket + 12V Socket



Operator Environment

E Class Air Conditioned Cab Mechanical Cabin Suspension Max-Professional Air Seat Tilt and Telescopic Steering Wheel SDD Rapid Steering Circuit Hi Visibility Glass Roof INFOCENTER Pro Digital Display COMFORTIP Sequential Drive System Satellite Armrest with MaxCom Joystick 4 Programmable Buttons on MaxCom Joystick Trainee Seat with Seatbelt MP3 Radio Player with Quad Speakers Telescopic Mirrors WOLP (Work Operating Light Panel) 8 Cabin Work Lights 2 Work Lights on Cab Post 4 Bonnet Front Work Lights Rotating Beacon

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
120 L/min Hyd Pump
Free Hydraulic Oil Return
4 Sets of Electro-Hyd Remotes with Float
Timer & Flow Control on All Remotes
AGROTRONIC EHR with Position & Draft
External Raise & Lower on Rear Fenders
Cat II Hook Ends
5000 kg Lift Capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase 2550 mm Length 4428mm Total Height 2740mm Total Weight 5850kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.