

AGROFARM G SERIES

ROPS & CAB

96 - 110^{HP}



A step up in power and comfort, the two Agrofarm G Series models are available as cabin or ROPS versions and produce 96 hp and 110 hp respectively. Designed for our variable Australian conditions, these superbly designed tractors are renowned their heavy-duty frame and manoeuvrability, a distinct advantage with a loader fitted.

Built for multi-purpose farming, they feature a high capacity hydraulic pump, 4 wheel independent wet disc brakes and choice of two transmission types, wet clutch Powershuttle or dry clutch synchro shuttle. Visibility is outstanding, likewise the torque developed by the Deutz-Fahr SDF 1000 Series 4 cylinder turbo intercooled engine. The Agrofarm G Series represents real value for money.



CABIN



ROPS



100DT

CAB

96HP

115GS

CAB

110HP

115GS

ROPS

110HP

DEUTZ-FAHR



1800 789 633

TECHNICAL DATA & FEATURES

AGROFARM 100DT CAB

AGROFARM 115GS CAB

AGROFARM 115GS ROPS

POWER + PERFORMANCE

Engine Type	Deutz-Fahr SDF 1000 Series		
Emissions	Tier I	Tier II	
Cylinders / Capacity	4/4000		
Aspiration	Turbo	Turbo Intercooler	
Max Power - ECE R120 (kW/HP)	70.6/96	81/110	
Max Torque (Nm)	342	396	
Rated Engine Speed (rpm)	2300	2350	
Fuel Capacity (l)	150		

DRIVE + HANDLING

Gearbox Type and Gears	Synchronised Shuttle	Wet Clutch Power Shuttle	
Number of Gears	20+20	30+30	40+40
Powershift Speeds	-	2	
Forward/Reverse Shuttle	■		
Clutch Type	Self-Adjusting Dry Heavy Duty 13"	Wet Clutch	
Min Speed (km/h)	0.20	2.01	0.22
Max Speed (km/h)	40		
4WD	■		
Diff Lock	Electro-Hyd Operated Front + Rear		
Brakes (NO / Type)	4/ Independent Wet Disc		
Wheel Size - Rear	Adjustable 480/70R34		
Wheel Size - Front	Adjustable 420/70R24		
PTO Type	Electro-Hyd Independent Wet Clutch		
Speeds - Rear	540/540E/1000/1000E		540/1000
PTO engine speed (rpm)	2077/1654/2250/1783		2077/2250

LIFT + FLOW

Type	Open Centre		
Flow Rate (Type + l/min)	Steering 44 / Hydraulic 56		
Remote Valves (sets)	2	3	
3 Point Hitch Type	Mechanical with Draft		
Category	2		
Hitch End Type	Hook		Ball
Max Lift Capacity - Rear (kg)	4200	4800	4200

COMFORT + CONVENIENCE

Air-Conditioned Cabin	■		-
Radio/MP3 Player	■		-
2 Post ROPS	-	-	■
Sun Canopy	-	-	■
Cloth Driver Seat w/ Pneumatic Suspension	■		-
PVC Driver Seat w/ Mechanical Suspension	-	-	■
Adjustable Steering Wheel	■		
Display	Analogue / Digital		
Side Control Levers	■		
Engine Speed Programming	-	■	
Flat Platform Mounted on Silent-Block	■		
Upswept Side Mounted Exhaust	■		
Worklights (No + Type)	2 Bonnet / 4 Cabin		2 Bonnet / 2 Rear

WEIGHTS + DIMENSIONS

Wheelbase (mm)	2310	2340	
Length (mm)	3850	3990	
Min Overall Width (mm)	2082		
Height (mm)	2790		2710
Weight (kg)	4100	4250	3650

■ Standard