

# Agrofarm G 115 GS



**Engine** 

SDF1000 Series Tier 2 Diesel Engine
4 Cyl/4000cc Turbocharged Intercooled
Liquid/Oil Cooled
Bosch High Pressure Individual Diesel Injection
110Hp @ 2350rpm (2005/25/CE)
Torque 396nm
Engine Speed Programming
Side Mounted Cabin Exhaust
160lt Fuel Capacity
Donaldson Air-cleaner with Extension

#### **Transmission**

40/40 Forward/Reverse Gears Wet Clutch Powershuttle 2 Speed Powershift Comfort Clutch Creep Gear Std Front Wheel Assist 4 Wheel Independent Braking 100% Front & Rear Diff Lock 40 km/h Road Speed

#### PTO

Independent wet multidisc clutch 2 Speed PTO 540-1000 1" 3/8 – 6 Spline PTO Shaft Push Button Control Interchangeable PTO Shaft Function

## Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment 420/70R24 Front -480/70R34 Rear

### **Operator Environment**

2 Post ROP Frame
Flat Floor ISO Mounted Platform
Rubber Floor Mat
Ergonomic Controls
Telescopic and Tilting Steering Wheel
Multi Function Digital Dash
Deluxe PVC Mechanical Seat
Sun Canopy
Telescopic Mirrors
2 Rear Canopy Work Lights
2 Bonnet Work Lights
Rotating Beacon

## Hyd/Linkage/Drawbar

Open Centre Hydraulic System
56 L/min Hyd Pump
Separate 44L/min Steering Pump
3 Set of Remotes –1 Kick out / 1 Detent / 1 Float
Flow control on one Remote
Mechanical Linkage c/w Position & Draft Controls
Cat 2 Ball Ends
4200kg lift Capacity
Swinging Drawbar – CAT A

# **Weights & Dimensions**

Wheelbase 2380mm Length 3950mm Total Height 2580mm Total Weight 3650kg

Specifications are accurate at time of printing: July 2022. PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.