## DEUTZ-FAHR AGROFARM G SERIES



A step up in power and comfort, the two Agrofarm G Series models are available as cabin or ROPS versions and produce 96 hp and 110 hp respectively. Designed for our variable Australian conditions, these superbly designed tractors are renowned their heavy-duty frame and manoeuvrability, a distinct advantage with a loader fitted.

Built for multi-purpose farming, they feature a high capacity hydraulic pump, 4 wheel independent wet disc brakes and choice of two transmission types, wet clutch Powershuttle or dry clutch synchro shuttle. Visibility is outstanding, likewise the torque developed by the Deutz-Fahr SDF 1000 Series 4 cylinder turbo intercooled engine. The Agrofarm G Series represents real value for money.







TECHNICAL DATA & FEATURES	AGROFARM 100DT CAB	AGROFARM 115GS CAB	AGROFARM 115GS ROPS
POWER + PERFORMANCE			
Engine Type		Deutz-Fahr SDF 1000 Series	
Emissions	Tier I	Tier II	
Cylinders / Capacity	4/4000		
Aspiration	Turbo	Turbo Interd	cooler
Max Power - ECE R120 (kW/HP)	70.6/96	81/110	)
Max Torque (Nm)	342 396		
Rated Engine Speed (rpm)	2300	2350	
Fuel Capacity (I)	150		
DRIVE + HANDLING		130	
	Synchronised Shuttle Wet Clutch Power Shuttle		
Gearbox Type and Gears  Number of Gears	-		40+40
	20+20	30+30	40+40
Powershift Speeds	-	2	
Forward/Reverse Shuttle			
Clutch Type	Self-Adjusting Dry Heavy Duty 13"	Wet Clut	 T
Min Speed (km/h)	0.20	2.01	0.22
Max Speed (km/h)	40		
4WD	•		
Diff Lock	Electro-Hyd Operated Front + Rear		
Brakes (N0 / Type)	4/ Independent Wet Disc		
Wheel Size - Rear	Adjustable 480/70R34		
Wheel Size - Front	Adjustable 420/70R24		
РТО Туре	Electro-Hyd Independent Wet Clutch		
Speeds - Rear	540/540E/1000/1000E 540/1000		
PTO engine speed (rpm)	2077/1654/2250/1783		2077/2250
LIFT + FLOW			
Туре	Open Centre		
Flow Rate (Type + I/min)		Steering 44 / Hydraulic 56	
Remote Valves (sets)	2 3		
3 Point Hitch Type	Mechanical with Draft		
Category	2		
Hitch End Type	Hook		Ball
Max Lift Capacity - Rear (kg)	4200	4800	4200
COMFORT + CONVENIENCE			
Air-Conditioned Cabin			-
Radio/MP3 Player			-
2 Post ROPS	-	-	•
Sun Canopy	-	-	
Cloth Driver Seat w/ Pneumatic Suspension	•		-
PVC Driver Seat w/ Mechanical Suspension	-	-	•
Adjustable Steering Wheel		•	<u> </u>
Display	Analogue / Digital		
Side Control Levers	■ ■		
Engine Speed Programming	_		
Flat Platform Mounted on Silent-Block			
Upswept Side Mounted Exhaust			
Worklights (No + Type)	2 Bonnet / 4		2 Bonnet / 2 Rear
WEIGHTS + DIMENSIONS	Z Boillet / Z	r CuDIII	Z DOINIEL / Z Nedi
	2310	2340	
Wheelbase (mm)			
Length (mm)	3850	3990	
Min Overall Width (mm)		2082	
Height (mm)	2790		2710
Weight ( <b>kg</b> )	4100	4250	3650
DELITZ-EAUD P	HONE 1800 789 633	Images for illustration	■ Standard  n purposes only. For exact specifications