Front Linkage + PTC

5110.4D TTV

Specialist Series

Engine

FARMotion Tier 4i Diesel Engine 4 Cyl/3849cc Turbocharged/Intercooled **Electronically Controlled** Emission Control by DOC unit Liquid/Oil Cooled Electronically Controlled E-Visco Fan High Pressure Diesel injection common rail 113 Hp Max hp @ 2200 rpm (2000/25/CE) 6 Hp Power Boost Torque 435 Nm @1600 rpm Programmable Engine Speed × 2 Powercore Air Filter with Dust Ejectors Side Vertical Exhaust Fuel Tank 115 Litres

Transmission

TTV 2 Range Variable Transmission 3 Modes (AUTO, Manual, PTO) Eco/Power Dial Speed Cruise Control × 2 Active Stationary Control (Power Zero) Wet Clutch Powershuttle Shuttle Modulation - 5 Stage (Sense Clutch) Front Wheel Assist - Push Button 4 Wheel Independent Braking Hydraulic Parking Brake (HPB) 100% Front & Rear Diff Lock - Push Button 40km/h Road Speed @ 1650 RPM

PTO

Independent Hydraulic Rear PTO Push Button Auto PTO Function 3 Speed PTO 540/750/1000 1" 3/8 - 6 Spline PTO Shaft Interchangeable PTO Spline Function

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment Front 320/85R20 Rear 380/85R30Rear Front Weight Frame with Hitch Rear Swinging Drawbar Battery Isolator Switch

Front Linkage & PTO

Front Linkage - 1750kg Capacity Front PTO - 1000N Push Button PTO Control Linkage Operated via Separate Remote Switch



Operator Environment

4 Post Air conditioned Cabin with CAT 4 Filtration Flat Operator Floor Rear Hinged Roof for High Visibility Hydro Silent Block Cabin Suspension Super Deluxe Air Seat with Tilt and Lumbar Support Tilt and Telescopic Steering Wheel Armrest Control with MaxCom Joystick 3 Programmable Buttons on MaxCom Joystick SDD Rapid Steering Circuit INFOCENTER Pro Digital Display COMFORTIP Sequential Drive System MP3 Radio Player with Speakers Telescopic Mirrors 6 Cabin Work Lights 4 Bonnet Front Work lights Rotating Beacon 2 External Electrical Sockets

Hyd/Linkage/Drawbar Closed Centre Hydraulic System 100 I/min Hydraulic Pump Electro Hyd Remotes Controlled on MaxCom Armrest 4 Sets of Rear High Flow Remotes 2 Sets of Front Remotes duplicated from Rear 1 Rear Free Flow Return 1 Front Free Flow Return Timer and Flow Control on All Remotes Separate 42L/min Steering Pump Electronic 3PL c/w Position & Draft Controls External Push button Raise and Lower Cat 2 Hook Ends 4310 kg Lift Capacity Swinging Drawbar - CAT A

Weights & Dimensions

Wheelbase 2271 mm Length 4060 mm Total Height 2545mm (Top of Cab) Min Overall Width 1780mm (Rear wheels) Cabin Width 1280mm Total Weight 4258kg

Specifications are accurate at time of printing: July 2022, PFG Australia Pty Ltd reserves the right to change std equipment at anytime without prior notice.