

# 5110.4 D TTV

## Specialist Series



### Engine

FARMotion Tier 4i Diesel Engine  
4 Cyl/3849cc Turbocharged/Intercooled  
Electronically Controlled  
Emission Control by DOC unit  
Liquid/Oil Cooled  
Electronically Controlled E-Visco Fan  
High Pressure Diesel injection common rail  
113 Hp Max hp @ 2200 rpm (2000/25/CE)  
6 Hp Power Boost  
Torque 435 Nm @1600 rpm  
Programmable Engine Speed × 2  
Powercore Air Filter with Dust Ejectors  
Side Vertical Exhaust  
Fuel Tank 115 Litres

### Transmission

TTV 2 Range Variable Transmission  
3 Modes (AUTO, Manual, PTO)  
Eco/Power Dial  
Speed Cruise Control × 2  
Active Stationary Control (Power Zero)  
Wet Clutch Powershuttle  
Shuttle Modulation – 5 Stage (Sense Clutch)  
Front Wheel Assist – Push Button  
4 Wheel Independent Braking  
Hydraulic Parking Brake (HPB)  
100% Front & Rear Diff Lock – Push Button  
40km/h Road Speed @ 1650 RPM

### PTO

Independent Hydraulic Rear PTO  
Push Button  
Auto PTO Function  
3 Speed PTO 540/750/1000  
1" 3/8 – 6 Spline PTO Shaft  
Interchangeable PTO Spline Function

### Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment  
Front 320/85R20 Rear 380/85R30Rear  
Front Weight Frame with Hitch  
Rear Swinging Drawbar  
Battery Isolator Switch

### Operator Environment

4 Post Air conditioned Cabin with CAT 4 Filtration  
Flat Operator Floor  
Rear Hinged Roof for High Visibility  
Hydro Silent Block Cabin Suspension  
Super Deluxe Air Seat with Tilt and Lumbar Support  
Tilt and Telescopic Steering Wheel  
Armrest Control with MaxCom Joystick  
3 Programmable Buttons on MaxCom Joystick  
SDD Rapid Steering Circuit  
INFOCENTER Pro Digital Display  
COMFORTIP Sequential Drive System  
MP3 Radio Player with Speakers  
Telescopic Mirrors  
6 Cabin Work Lights  
4 Bonnet Front Work lights  
Rotating Beacon  
2 External Electrical Sockets

### Hyd/Linkage/Drawbar

Closed Centre Hydraulic System  
100 l/min Hydraulic Pump  
Electro Hyd Remotes Controlled on MaxCom Armrest  
3 Sets of Rear High Flow Remotes  
1 Free Flow Return  
Timer and Flow Control on All Remotes  
Separate 42L/min Steering Pump  
Electronic 3PL c/w Position & Draft Controls  
External Push button Raise and Lower  
Cat 2 Hook Ends  
4310 kg Lift Capacity  
Swinging Drawbar – CAT A

### Weights & Dimensions

Wheelbase 2271 mm  
Length 4060 mm  
Total Height 2545mm (Top of Cab)  
Min Overall Width 1780mm (Rear wheels)  
Cabin Width 1280mm  
Total Weight 4058kg