

SOLIS PRIME.



S26 SHUTTLE XL

26HP
ROPS

ENGINE

Mitsubishi Stage V Diesel Engine
Water Cooled with vertical overhead valve
3 Cylinder/1319 cc Naturally Aspirated
26 Hp @ 2500 RPM
76.3 Nm Max Torque
Dry air cleaner with clogging sensor
Downswept exhaust with silencer under hood
22 Lt fuel tank capacity

TRANSMISSION

Synchronised Shuttle Transmission
9 Forward gears + 9 Reverse gears
Forward/Reverse LH Shuttle lever
Single dry clutch
1.14 km/M in Speed
21.46km/h Max speed
2WD + 4WD Modes - Mechanical
Rear Diff Lock - Mechanical
Rear oil immersed brakes
Mechanical hand brake

PTO

2 Speed PTO
540 + 540E
540 @ 2565 engine rpm
540E @ 2083 engine rpm
Electro hydraulic engagement
Mechanical selector lever
PTO safety switch

OPERATING AREA

Foldable rear mounted 2 Post ROPS
Mono block mounted semi flat platform
Rubber floor mat
Adjustable deluxe mechanical suspended seat
Seat equipped with Headrest, Armrests + seatbelt
Analogue dash with digital hour meter
Ergonomic controls

ELECTRICAL

12V -65Ah Battery
12V - 42 Amp Alternator
Battery isolator switch
2 Bonnet headlights with Hi/lo beam
Front park lights
Front and rear Indicators
Rear brake and tail lights
Rear work light
Rotary Beacon
7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics
16.5 litres per minute flow
Rear remotes - 1 set
CAT 1-N Rear 3-point linkage
600kg capacity
Mechanical right-hand side lever control
Adjustable sway bars
Rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Galaxy Pro fixed wheel/tyre package
220/55R12 Front tyres
280/70R16 Rear tyres
Wheelbase - 1590mm
Total length with loader - 3850mm
Total width - 1290mm
Total height - 2280mm
Min ground clearance - 190mm
Front track - 950mm
Rear track - 995mm
Tractor weight fitted with loader -1435kg TBC

FRONT END LOADER

SOLIS/TITAN 3200 XL Level lift loader
Integrated loader joystick and valve
Electric diverter 3rd function
1.35mt 4in1 bucket
SOLIS EASY Vision quick change EURO hitch
Lift Height @ Bucket Pivot point - 2170mm
Lift Height @ bottom of Bucket - 1950mm
Dump clearance - 1635mm
Dump angle - 45 degrees
Crowd angle @ ground level - 43 degrees
Crowd angle @ full height - 47 degrees
ROL with No Ballast - 365kg
ROL with 250kg ballast - 475kg