

# SOLIS PRIME

## H26 HST



**26HP**  
**ROPS**

### ENGINE

Mitsubishi Stage V Diesel Engine  
Water Cooled with vertical overhead valve  
3 Cylinder/1319 cc Naturally Aspirated  
26 Hp @ 2500 RPM  
76.3 Nm Max Torque  
Dry air cleaner with clogging sensor  
Downswept exhaust with silencer under hood  
22 Lt fuel tank capacity

### TRANSMISSION

2 Range Hydrostatic transmission  
Side by Side Hydrostatic Pedals  
Min Speed 3.18km/h  
Max Speed 21km/h  
Cruise Control  
2WD + 4WD Modes - Mechanical  
Rear Diff Lock - Mechanical  
Rear oil immersed brakes  
Mechanical hand brake

### PTO

2 Speed PTO  
Rear - 540 Speed  
Mid - 2100 Speed  
Electro hydraulic engagement  
Mechanical selector lever  
PTO safety switch

### OPERATING AREA

Foldable rear mounted 2 Post ROPS  
Mono block mounted semi flat platform  
Rubber floor mat  
Adjustable deluxe mechanical suspended seat  
Seat equipped with Headrest, Armrests + seatbelt  
Analogue dash with digital hour meter  
Ergonomic controls

### ELECTRICAL

12V -65Ah Battery  
12V - 42 Amp Alternator  
Battery isolator switch  
2 Bonnet headlights with Hi/lo beam  
Front park lights  
Front and rear Indicators  
Rear brake and tail lights  
Rear work light  
Rotary Beacon  
7 Pin trailer socket

### HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics  
Hydraulic Pump Capacity 16.5 LPM  
Rear remotes - 1 set  
CAT 1-N Rear 3-point linkage  
600kg capacity  
Mechanical right-hand side lever control  
Adjustable sway bars  
Rear drawbar

### WHEELS/DIMENSIONS/WEIGHTS

Galaxy Pro fixed wheel/tyre package  
220/55R12 Front tyres  
280/70R16 Rear tyres  
Wheelbase - 1590mm  
Total length with loader - 3850mm  
Total width - 1290mm  
Total height - 2280mm  
Min ground clearance - 190mm  
Front track - 950mm  
Rear track - 995mm  
Tractor weight fitted with loader - 1470kg

### FRONT END LOADER

SOLIS/TITAN 3200 EH Level lift loader  
Integrated loader joystick and valve  
Electric diverter 3rd function  
1.35mt 4in1 bucket  
SOLIS EASY Vision quick change EURO hitch  
Lift Height @ Bucket Pivot point - 2170mm  
Lift Height @ bottom of Bucket - 1950mm  
Dump clearance - 1635mm  
Dump angle - 45 degrees  
Crowd angle @ ground level - 43 degrees  
Crowd angle @ full height - 47 degrees  
ROL with No Ballast - 235kg  
ROL with 250kg ballast - 300kg