

# SOLIS

## S60



## 60HP ROPS

### ENGINE

ITL 4100 FL Diesel Engine  
Water Cooled  
4Cylinder/3707cc Naturally Aspirated  
60 Hp @ 2200 RPM  
230 Nm Max Torque  
Dual dry air cleaner with clogging sensor  
Upswept exhaust with silencer under hood  
64 Lt fuel tank capacity

### TRANSMISSION

Synchronised Shuttle Transmission  
12 Forward gears + 12 Reverse gears  
Forward/Reverse LH Shuttle lever  
Double dry clutch  
35km/h Gearbox  
4WD Mode - Mechanical lever engagement  
Front Axle Power steering  
Rear Diff Lock - Mechanical foot pedal  
Rear oil immersed brakes  
Mechanical hand brake

### PTO

2 Speed Rear PTO  
540 + 540 Economy Speed  
540 @ 1938 engine rpm  
540 ECO @ 1646 engine rpm  
Mechanical lever engagement  
Mechanical selector lever

### OPERATING AREA

Foldable rear mounted 2 Post ROPS  
Semi flat platform  
Rubber floor mat  
Front noise/mud deflectors  
Adjustable mechanical suspended seat  
Seat equipped with seatbelt  
Analogue dash with digital hour meter  
Ergonomic controls  
Sun Canopy

### ELECTRICAL

12V -110Ah Battery  
12V - 90 Amp Alternator  
Battery isolator switch  
2 Bonnet headlights with Hi/lo beam  
4 Canopy work lights  
Front park lights  
Front and rear indicators  
Rear brake and tail lights  
Rear work light  
Rotary Beacon  
7 Pin trailer socket

### HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics  
Hydraulic Pump Capacity - 31.7 LPM  
Rear remotes - 2 sets Double Acting  
Hydraulic Flow @ remote 44 LPM  
CAT 2 Rear 3-point linkage  
RH Position and Draft Levers  
Quick hitch hook ends  
2500kg capacity  
Adjustable sway bars  
Swinging rear drawbar

### WHEELS/DIMENSIONS/WEIGHTS

Radial Ag tyre and wheel package  
250/85R20 Front tyres  
340/85R28 Rear tyres  
Front dynamic steering fenders  
Wheelbase - 2200mm  
Total length with loader -  
Total width - 1820-2250  
Total height - 2610mm  
Min ground clearance - 307  
Front track -1500-1940mm  
Rear track -1350-1890mm  
Tractor weight - 2900kg

### FRONT END LOADER

SOLIS/TITAN 7300 Level lift loader  
Single lever joystick and valve  
Electric diverter 3rd function  
1.8mt 4in1 bucket  
SOLIS EASY Vision quick change EURO hitch  
Lift Height @ Bucket Pivot point - 3110mm  
Lift Height @ bottom of Bucket - 2770mm  
Dump clearance - 2200mm  
Dump angle - 59 degrees  
Crowd angle @ ground level - 45 degrees  
Crowd angle @ full height - 48 degrees  
ROL with No Ballast - kg  
ROL with 250kg ballast - kg