

SOLIS PRIME.

S60 SHUTTLE XL

**60HP
CAB**



ENGINE

ITL Stage V Water Cooled Diesel Engine
Common Rail
3 Cylinder turbocharged intercooled / 3065cc
60 Hp @ 2200 RPM
250 Nm Max Torque @ 1400 RPM
DOC after treatment system
Dual dry air cleaner with clogging sensor
Upswept exhaust with silencer under hood
72 Lt fuel tank capacity

TRANSMISSION

Synchronised Shuttle Transmission
12 Forward gears + 12 Reverse gears
Forward/Reverse LH Shuttle lever
Double dry clutch
35km/h Gearbox
4WD Mode - Mechanical lever engagement
Front Axle Power steering
Rear Diff Lock - Mechanical foot pedal
Rear oil immersed brakes
Mechanical hand brake

PTO

2 Speed Rear PTO
540 + 540 Economy Speed
Mechanical lever engagement
Mechanical selector lever

OPERATING AREA

S Comfort premium operator's package
Solis H Type Cabin with ROPS protection
Digital Climate Control with A/C & Heater
Deluxe Mechanical Cloth Seat with seatbelt
Analogue/Digital Dash
Adjustable Steering wheel
Ergonomic Controls
Rear Left hand workstation
Internal rear-vision mirror
Front and Rear wiper with washer

ELECTRICAL

12V -110Ah Battery
12V - 90 Amp Alternator
Battery isolator switch
2 Bonnet headlights with Hi/lo beam
4 Cabin work lights
Front park lights
Front and rear indicators
Rear brake and tail lights
Rear work light
Rotary Beacon
7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics
Hydraulic Pump Capacity - 45 LPM
Rear remotes - 2 sets Double Acting
1 Detent / 1 Float
CAT 2 Rear 3-point linkage
RH Position and Draft Levers
CAT 2 Ball ends
2500kg capacity
Adjustable sway bars
Swinging rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Radial Ag tyre and wheel package
250/85R24 Front tyres
420/85R28 Rear tyres
Front dynamic steering fenders
Wheelbase - 2220mm
Total length with loader - TBC
Total width - 1865
Total height - 2485
Min ground clearance - 366
Front track - 1550
Rear track - 1450
Tractor weight - 3140kg

FRONT END LOADER

SOLIS/TITAN 7300 Level lift loader
Single lever joystick and valve
Electric diverter 3rd function
1.8mt 4in1 bucket
SOLIS EASY Vision quick change EURO hitch
Lift Height @ Bucket Pivot point - 3110mm
Lift Height @ bottom of Bucket - 2770mm
Dump clearance - 2200mm
Dump angle - 59 degrees
Crowd angle @ ground level - 45 degrees
Crowd angle @ full height - 48 degrees