





ENGINE

ITL Stage V Water Cooled Diesel Engine Common Rail 4 Cylinder turbocharged intercooled / 3065cc 75 Hp @ 2200 RPM DOC after treatment system Dual dry air cleaner with clogging sensor Upswept exhaust with silencer under hood 72 Lt fuel tank capacity

TRANSMISSION

Synchronised Shuttle Transmission 12 Forward gears + 12 Reverse gears Forward/Reverse LH Shuttle lever Double dry clutch 35km/h Gearbox 4WD Mode - Mechanical lever engagement Front Axle Power steering Rear Diff Lock - Mechanical foot pedal Rear oil immersed brakes Mechanical hand brake

ΡΤΟ

2 Speed Rear PTO 540 + 540 Economy Speed Mechanical lever engagement Mechanical selector lever

OPERATING AREA

S Comfort premium operator's package Solis H Type Cabin with ROPS protection Digital Climate Control with A/C & Heater Deluxe Mechanical Cloth Seat with seatbelt Analogue/Digital Dash Adjustable Steering wheel Ergonomic Controls Rear Left hand workstation Internal rear-vision mirror Front and Rear wiper with washer

ELECTRICAL

12V -110Ah Battery 12V - 90 Amp Alternator Battery isolator switch 2 Bonnet headlights with Hi/lo beam 4 Cabin work lights Front park lights Front and rear indicators Rear brake and tail lights Rear work light Rotary Beacon 7 Pin trailer socket

HYDRAULICS/3-POINT LINKAGE/HITCH

Open Centre Hydraulics Hydraulic Pump Capacity - 37.6 LPM Rear remotes - 2 sets Double Acting CAT 2 Rear 3-point linkage RH Position and Draft Levers CAT 2 Ball ends 2500kg capacity Adjustable sway bars Swinging rear drawbar

WHEELS/DIMENSIONS/WEIGHTS

Radial Ag tyre and wheel package 320/85R24 Front tyres 460/85R30 Rear tyres Front dynamic steering fenders Wheelbase - 2350 Total length with loader - TBC Total width - 2050-2080 Total height - TBC Min ground clearance - 390-420 Front track - 1650-1850 Rear track - 1500-1700 Tractor weight - 3645 TBC

FRONT END LOADER

SOLIS/TITAN 8300 Level lift loader Single lever joystick and valve Electric diverter 3rd function 1.8mt 4in1 bucket SOLIS EASY Vision quick change EURO hitch Lift Height @ Bucket Pivot point - 3460mm Lift Height @ bottom of Bucket -3120mm Dump clearance - 2560mm Dump angle - 54 degrees Crowd angle @ ground level - 46 degrees Crowd angle @ full height - 48 degrees



L 1800 959 591